

# GSL ENERGY

Much More Than Grade A



51.2V 200Ah

UL1973

CEC



As the leading vertically integrated manufacturer of lithium iron phosphate battery systems, GSL ENERGY has provided various battery solutions for nearly all kinds of ESS applications. Thanks to our self-developed core technology in cells/BMS/system design, GSL ENERGY has delivered more than 138+ countries serving 100,000+ users.

[www.gsl-energy.com](http://www.gsl-energy.com)

## ✓ Long life and safety

Vertical industry integration ensures more than 8500 cycles with 80% DoD.  
Safe Lithium iron phosphate battery cell.

## ✓ Intelligent

Each battery with independent BMS system manages power output smartly and effectively.

## ✓ Modularization

Modular design gives the end customers the power of choice of capacity Deliver up to 163KW with single max module (10.24KWh) at 16pcs parallel connection.

## ✓ Easy to install and use

Just plug and play to minimize the installation time and cost. Compact and fashionable design fits in your sweet home environment.

## ✓ Compatibility

Compatible with most of the available Hybrid inverters.

## ✓ Safety Cert

UL1973, CE-EMC, UN38.3, MSDS

Battery Specifications		
Model No		GSL-051200A-B-GBP2
Nominal Parameters		
Battery Chemistry		LiFePO4
Voltage		51.2V
Operating Voltage		46-56V
Capacity		200Ah
Energy		10.24Kwh
Scalability		Max.16pcs in parallel (162kWh)
Usable Energy		9.22Kwh
Charge/Discharge Current	Recommend	100A
	Max.	150A
	Peak(2mins,25℃)	200A
Basic Parameters		
Recommend Depth of Discharge		90%
Dimension (W/H/D)		780*550*200mm / 30.7*21.6*7.8 in
Weight Approximate		102.5kgs / 225 lbs
Master LED Indicator		4 LED (SOC:25%~100%)
		2 LED (working, alarming, protecting)
IP Rating of Enclosur		IP20
Working Temperature		Charge:0℃ ~ 55℃ Discharge:-20℃ ~ 55℃
Storage Temperature		0℃ ~ 35℃
Humidity		5%~95%
Altitude		≤2000m
Cycle Life (25±2℃,0.5C/0.5C,80%EOL)		≥6500
Installation		Wallmounted
Communication Port		CAN2.0, RS485
Warranty Period [3]		15 years
Life Cycle Power During Warranty Period		44.84MWh@80% EOL
Certification		UL1973, CE-EMC, UN38.3, MSDS